



JDYX.E115701 Fuses, Supplemental

If you notice a change to your JDYX Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Fuses, Supplemental

[See General Information for Fuses, Supplemental](#)

JENN FENG ELECTRIC INDUSTRIAL CO LTD

E115701

1308-3 Zhongshan Rd
Taoyuan District
Taoyuan, 33057 TAIWAN

Supplemental fuses: pigtail leads, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MFG46-PA	4.6 x 14.5 (0.18 x 0.57)	0.125 - 0.25	125Vac	10000
		0.125 - 0.25	250Vac	35
		0.1	125Vac	10000
		0.1	250Vac	35

Supplemental fuses: pigtail leads, time delay, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MSG63-PA	6.35 x 31.75 (0.25 x 1.25)	0.0625 - 1.0	125Vac	10000
		0.0625 - 1.0	250Vac	35
		1.25 - 2.5	125Vac	10000
		1.25 - 2.5	250Vac	100
		3	125Vac	10000
		3	250Vac	100
		4 - 8	125Vac	10000
		4 - 8	250Vac	200
		9 - 10	125Vac	10000
		9 - 10	250Vac	200

Supplemental fuses: cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MFA	6.35 x 31.8 (0.25 x 1.25)	0.1 - 10	125Vac	10000
		0.1 - 1	250Vac	35

		1.2 - 3.5	250Vac	100
		4 - 10	250Vac	200
MFC63	6.35 x 31.8 (0.25 x 1.25)	0.25 - 15	125Vac	10000
		0.25 - 1	250Vac	35
		1.125 - 3.5	250Vac	100
		4 - 10	250Vac	200
		12 - 15	250Vac	750
MFG	5.2 x 20 (0.20 x 0.79)	0.1 - 10	125Vac	10000
		0.1 - 1	250Vac	35
		1.2 - 3.5	250Vac	100
		4 - 8	250Vac	200
MFG16	6.35 x 15.9 (0.25 x 0.63)	0.1 - 0.75	125Vac	10000
		0.1 - 0.75	250Vac	35
		1	125Vac	10000
		1	250Vac	35
		1.125 - 3.5	125Vac	10000
		1.125 - 3.5	250Vac	100
MFG25	6.35 x 25.4 (0.25 x 1.00)	0.25 - 10	125Vac	10000
		0.25 - 1	250Vac	35
		1.125 - 3.5	250Vac	100
		4 - 10	250Vac	200
MFG46	4.6 x 14.5 (0.18 x 0.57)	0.1 - 0.2	125Vac	10000
		0.1 - 0.2	250Vac	35
		0.2	350Vac	100
		2.0	125Vac	10000
		2.0	250Vac	100
		2.25 - 7.0	125Vac	10000
MMG52	5.2 x 20 (0.20 x 0.79)	0.063 - 1	125Vac	10000
		0.063 - 1	250Vac	35
		1.25 - 3.5	125Vac	10000
		1.25 - 3.5	250Vac	100
		4 - 10	125Vac	10000
		4 - 10	250Vac	200
MMG63	6.35 x 31.8 (0.25 x 1.25)	1	125Vac	10000
		1	250Vac	35
MSG52	5.2 x 20 (0.20 x 0.79)	0.063 - 6	125Vac	10000

		0.063 - 0.4	250Vac	35
--	--	-------------	--------	----

Supplemental fuses: pigtail leads, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MFA-P	6.35 x 31.8 (0.25 x 1.25)	0.1 - 10	125Vac	10000
		0.1 - 1	250Vac	35
		1.2 - 3.5	250Vac	100
		4 - 10	250Vac	200
MFA-P% , % represents A or R				
	7 x 32.6 (0.28 x 1.28)	0.1 - 10	125Vac	10000
		0.1 - 1	250Vac	35
		1.2 - 3.5	250Vac	100
		4 - 10	250Vac	200
MFC63-P	6.35 x 31.8 (0.25 x 1.25)	0.25 - 15	125Vac	10000
		0.25 - 1	250Vac	35
		1.125 - 3.5	250Vac	100
		4 - 10	250Vac	200
		12 - 15	250Vac	750
MFC63-P% % represents A or R				
	6.85 x 32.6 (0.27 x 1.28)	0.25 - 15	125Vac	10000
		0.25 - 1	250Vac	35
		1.125 - 3.5	250Vac	100
		4 - 10	250Vac	200
		12 - 15	250Vac	750
MFG-P	5.2 x 20 (0.20 x 0.79)	0.1 - 10	125Vac	10000
		0.1 - 1	250Vac	35
		1.2 - 3.5	250Vac	100
		4 - 8	250Vac	200
MFG-P% % represents A or R				
	5.9 x 24 (0.23 x 0.94)	0.1 - 10	125Vac	10000
		0.1 - 1	250Vac	35
		1.2 - 3.5	250Vac	100
		4 - 8	250Vac	200
MMG52-P% % represents A or R				
	5.9 x 24 (0.23 x 0.94)	0.063 - 1	125Vac	10000
		0.063 - 1	250Vac	35

		1.25 - 3.5	125Vac	10000
		1.25 - 3.5	250Vac	100
		4 - 10	125Vac	10000
		4 - 10	250Vac	200
MMG63-P% % represents A or R				
	7 x 32.6 (0.28 x 1.28)	1	125Vac	10000
		1	250Vac	35
MSG52-P% % represents A or R				
	5.9 x 24 (0.23 x 0.94)	0.063 - 6	125Vac	10000
		0.063 - 0.4	250Vac	35

Supplemental fuses: time delay, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MSG63	6.35 x 31.75 (0.25 x 1.25)	0.0625 - 1.0	125Vac	10000
		0.0625 - 1.0	250Vac	35
		1.25 - 2.5	125Vac	10000
		1.25 - 2.5	250Vac	100
		3	250Vac	100
		3	125Vac	10000
		4 - 8	125Vac	10000
		4 - 8	250Vac	200
		9 - 10	125Vac	10000
		9 - 10	250Vac	200

Supplemental micro fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MFP50, MFP51@, MSP50, MSP51@				
	8.5 x 7.5 x 0.75 (0.33 x 0.30 x 0.03)	0.1 - 6.3	125Vac	50
		0.1 - 6.3	250Vac	50

Supplemental micro fuses: cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MFH	3.6 x 10 (0.14 x 0.39)	0.1 - 0.8	250Vac	50
		1 - 10	250Vac	50
		0.1 - 0.8	125Vac	50
		1 - 15	125Vac	50

Supplemental micro fuses: pigtail leads, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
MFH-P	3.6 x 10 (0.14 x 0.39)	0.1 - 0.8	250Vac	50
		1 - 10	250Vac	50
		0.1 - 0.8	125Vac	50
		1 - 15	125Vac	50
MFH-P% % represents A or R				
	4 x 11 (0.16 x 0.43)	0.1 - 0.8	250Vac	50
		1 - 10	250Vac	50
		0.1 - 0.8	125Vac	50
		1 - 15	125Vac	50

Last Updated on 2017-08-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".